

General Information**19583 4 Ply Tan Nylon Sliptop C X FS**

MWR Part#	19583
Description	4 ply Tan Nylon Sliptop C X FS
Additional Specifications	10704 #32
Special features	The hard-woven, abrasive-resistant bare nylon top surface is virtually frictionless
Product Category	General Transportation
Main industry segments	Suitable for a variety of industries, including bottling, logistics, agriculture, automotive, building materials, carton and paper packaging, chemicals, cutting, electronics, feed, industrial, lumber, manufacturing, materials handling, municipalities, optical, package handling, parcel handling, plastics, printing, textiles & sports and leisure.
Applications	Ideal for "stall" operations or accumulating applications where the product must stop while the belt continues to move. Commonly used with automatic packaging machinery and with gates or diverter arms.

**Product Construction Design**

Top Cover Compound	Tan Hard-Woven Nylon
Top Cover Description	Bare
Bottom Cover Compound	Tan Nitrile
Bottom Cover Description	Friction Surface
Carcass Type	Polyester
Carcas Compound	Tan Nitrile
Number of Plies	4

Product Characteristics

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Technical Data

Minimum Pulley Diameter	2.00 in
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Overall Gauge (in)	(3.18 mm) 1/8 in
Unit Weight- lb/PIW	0.0700 lbs/PIW
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	-20 °F
Tension Rating (PIW)	48 PIW

Joining Related Properties

Splice Step	Yes
Splice Finger	No
Flexco Plate/Rivet	
Flexco Hinged	
Alligator Staple	#62
Clipper Lace	#1
Alligator Lace	#15



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

www.midwestrubber.com