

General Information

20256 3 Ply Blue Carbox Nitrile 150 Roughtop C X B

| | |
|---------------------------|--|
| MWR Part# | 20256 |
| Description | 3 Ply Blue Carbox Nitrile 150 Roughtop C X B |
| Additional Specifications | 10662 #61A |
| Special features | Carbox nitrile roughtop yields longer service life than rubber roughtop. |
| Product Category | Light duty |
| Main industry segments | automotive, pharmaceuticals, printing and paper, agriculture, bottling, building materials manufacturing, carton and paper packaging, chemicals, cutting, electronics, elevator and milling, feed, industrial, kitchen, logistics, lumber, manufacturing, marble and ceramic, materials handling, optical, packaging, parcel handling, package handling, waste and recycling and sports and leisure. |
| Applications | Ideal where regular roughtop surfaces wear down quickly and must be replaced. This belt is popular for handling cardboard cartons. |

Product Construction Design

| | |
|--------------------------|---------------------|
| Top Cover Compound | Blue Carbox Nitrile |
| Top Cover Description | Roughtop |
| Bottom Cover Compound | Bare RFL |
| Bottom Cover Description | Bare |
| Carcass Type | Polyester |
| Carcas Compound | Blue Carbox Nitrile |
| Number of Plies | 3 |

Product Characteristics

| | |
|-------------------|-----|
| Static Conducting | No |
| Cross Rigid | No |
| High Heat | No |
| Impression Top | Yes |
| Oil Resistant | Yes |
| Fire Resistant | No |
| FDA Approved | No |

Technical Data

| | |
|------------------------------|-------------------|
| Minimum Pulley Diameter | 2.50 in |
| Top Cover Thickness (in) | (0.00 mm) 0.00 in |
| Bottom Cover Thickness (in) | (0.00 mm) 0.00 in |
| Overall Gauge (in) | 9/32 in |
| Unit Weight- lb/PIW | 0.1130 lbs/PIW |
| Temperature Range (°F)- High | 250 °F |
| Temperature Range (°F)- Low | 0 °F |
| Tension Rating (PIW) | 150 PIW |

Joining Related Properties

| | |
|--------------------|------|
| Splice Step | Yes |
| Splice Finger | No |
| Flexco Plate/Rivet | #2 |
| Flexco Hinged | |
| Alligator Staple | #125 |
| Clipper Lace | |
| Alligator Lace | #15 |



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

WWW.midwestrubber.com