

**General Information****2249 1 Ply Black PVC 120 Smooth C X FS**

MWR Part#	2249
Description	1 Ply Black PVC 120 Smooth C X FS
Additional Specifications	10898 #91
Special features	
	Low stretch, high fastener holding ability. Superior rip, tear, and gouge resistance. Coefficient of Friction on Steel: Top Cover 0.8 / Bottom Cover 0.35
Product Category	PVC General
Main industry segments	Aviation, optical, package handling, agriculture, automotive, carton and paper packaging, cellulose, ceramic, chemicals, elevator and milling, feed, industrial, logistics, lumber, manufacturing, marble and ceramic, packaging, parcel handling and waste & recycling.
Applications	Has proven to be the longest wearing, best performing, most problem free package handling belt available today. Economical, general purpose specifications ideal for a variety of slider bed, applications.

**Product Construction Design**

Top Cover Compound	Black PVC
Top Cover Description	Smooth
Bottom Cover Compound	Woven Poly
Bottom Cover Description	Brushed
Carcass Type	Interwoven Polyester
Carcas Compound	Black PVC
Number of Plies	1

**Product Characteristics**

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

**Technical Data**

Minimum Pulley Diameter	2.50 in
Top Cover Thickness (in)	
Bottom Cover Thickness (in)	
Overall Gauge (in)	1/8 in
Unit Weight- lb/PIW	0.0700 lbs/PIW
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F
Tension Rating (PIW)	120 PIW

**Joining Related Properties**

Splice Step	No
Splice Finger	Yes
Flexco Plate/Rivet	
Flexco Hinged	
Alligator Staple	#125
Clipper Lace	#2
Alligator Lace	#15



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

[WWW.midwestrubber.com](http://WWW.midwestrubber.com)