

General Information

25052 2 Ply Green PVC Smooth C X B

MWR Part#	25052
Description	2 Ply Green PVC Smooth C X B
Additional Specifications	10812 #111A
Special features	general-purpose belt features a smooth PVC top cover and an anti-static carcass
Product Category	Material Handling
Main industry segments	waste & recycling, agriculture, bottling, carton and paper packaging, cellulose, logistics, manufacturing, marble and ceramic, materials handling, package handling, packaging, pharmaceutical, plastics, printing & paper and textiles.
Applications	Its dimensional stability and strength make it suitable for a wide range of industrial applications

Product Construction Design

Top Cover Compound	PVC
Top Cover Color	Petrol Green
Top Cover Description	Gloss Shore 80
Bottom Cover Compound	Polyester
Bottom Cover Description	Bare
Carcass Type	Polyester
Carcas Compound	PVC
Number of Plies	2

Product Characteristics

Static Conducting	Yes
Cross Rigid	Yes
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Technical Data

Minimum Pulley Diameter	A) Normal Flex (30.00 mm) 1.1811 in B) Back Flex (50.00 mm) 1.9685 in
Top Cover Thickness (in)	(0.50 mm) 0.0196 in
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in
Overall Gauge (in)	(2.00 mm) 0.0787 in
Unit Weight- lb/PIW	0.0358 lbs/PIW
Temperature Range (°F)- High	176 °F
Temperature Range (°F)- Low	5 °F
Tension Rating (PIW)	Pull for 1% Elongation(8 N/mm) 46 lbs/sq in

Joining Related Properties

Splice Step	No
Splice Finger	Yes
Foil	Yes
Press Temperature	330 °F
Press Pressure (psi)	25 lbs/sq in



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

WWW.midwestrubber.com