

**General Information****707-C 1 Ply Blue PVC 120 Glossy C X FS**

MWR Part#	707-C
Description	1 Ply Blue PVC 120 Glossy C X FS
Additional Specifications	SSW 120-E CXF CANNERS BB FDA
Applications	Abrasive products
Product Category	Packaged conveying
Main industry segments	Easy to fabricate
Special features	

**Product Construction Design**

Conveying side material	PVC 80 A
Conveying side surface	Glossy
Conveying side property	
Conveying side color	Light Blue
Traction layer (material)	Spun polyester (Weft: Flexible spun (PET))
Number of Plies	1
Pulley side material	PVC
Pulley side surface	Friction
Pulley side property	
Pulley side color	Light Blue

**Product Characteristics**

Antistatically equipped	No
Food suitability, FDA conformance	Yes

**Technical Data**

Thickness of belt	3.20 mm, 0.126 in
Mass of belt (belt weight)	3.5 kg/m <sup>2</sup> , .7169 lbs/ft <sup>2</sup>
Elongation at 2%	21 N/mm, 120 lbs/in
Min. operating temperature	0 °F, -18 °C
Max. operating temperature	180°F, 82 °C
Seamless manufacturing width	1829 mm, 72 in

**Joining Related Properties**

Primary Joining method	Finger (Finger Width 20 mm x Finger Length 80mm)
Secondary Joining method	Clipper® G Series™ G006, Alligator® Staple RS125, Alligator® 7
Front Flex Minimum Pulley	2.0 in, 51 mm
Back Flex Minimum Pulley	3.0 in, 76 mm

**Application Suitability**

Slider bed suitable	Yes
Carrying rollers suitable	Yes
Troughed installation suitable	Yes
Accumulator conveying	Yes
Metal Detectable	Yes



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

[WWW.midwestrubber.com](http://WWW.midwestrubber.com)