

General Information

710 2 Ply Tan GUM 160 Roughtop C X B

| | |
|---------------------------|---|
| MWR Part# | 710 |
| Description | 2 Ply Tan GUM 160 Roughtop C X B |
| Additional Specifications | 10616 #59A |
| Special features | The tan color is non-marking. The genuine gum is a soft durometer for the highest grab. |
| Product Category | Material Handling Incline Belt |
| Main industry segments | Agriculture, automotive, bottling, building materials manufacturing, carton and paper packaging, chemicals, cutting, electronics, elevator and milling, feed, industrial, kitchen, logistics, lumber, manufacturing, marble and ceramic, materials handling, optical, package handling, parcel handling, pharmaceuticals, printing and paper, waste and recycling and sports and leisure. |
| Applications | Ideal for the steep inclines and long wear in demanding applications. |

Product Construction Design

| | |
|--------------------------|-----------|
| Top Cover Compound | Tan NR |
| Top Cover Description | Roughtop |
| Bottom Cover Compound | Tan NR |
| Bottom Cover Description | Bare |
| Carcass Type | Polyester |
| Carcas Compound | Tan NR |
| Number of Plies | 2 |

Product Characteristics

| | |
|-------------------|-----|
| Static Conducting | No |
| Cross Rigid | No |
| High Heat | No |
| Impression Top | Yes |
| Oil Resistant | No |
| Fire Resistant | No |
| FDA Approved | No |

Technical Data

| | |
|------------------------------|-------------------|
| Minimum Pulley Diameter | 3.00 in |
| Top Cover Thickness (in) | |
| Bottom Cover Thickness (in) | |
| Overall Gauge (in) | 9/32 in (7.14 mm) |
| Unit Weight- lb/PIW | 0.1000 lbs/PIW |
| Temperature Range (°F)- High | 250 °F |
| Temperature Range (°F)- Low | -40 °F |
| Tension Rating (PIW) | 160 PIW |

Joining Related Properties

| | |
|--------------------|------|
| Splice Step | Yes |
| Splice Finger | No |
| Flexco Plate/Rivet | |
| Flexco Hinged | |
| Alligator Staple | #125 |
| Clipper Lace | #1 |
| Alligator Lace | #1 |



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

WWW.midwestrubber.com