

General Information

511 2 Ply Tan SBR 150 Roughtop C X B

MWR Part#	511
Description	2 Ply Tan SBR 150 Roughtop C X B
Additional Specifications	10610 #55
Special features	Non-markings and constructed of two plies of high-strength, all-synthetic polyester fabrics. Very flexible, low stretch and moisture resistant
Product Category	Incline Belt
Main industry segments	Agriculture, automotive, bottling, building materials manufacturing, carton and paper packaging, chemicals, cutting, electronics, elevator and milling, feed, industrial, kitchen, logistics, lumber, manufacturing, marble and ceramic, materials handling, optical, package and parcel handling, pharmaceuticals, printing and paper, waste and recycling, sports and leisure.
Applications	Ideal for incline/decline

Product Construction Design

Top Cover Compound	Tan SBR
Top Cover Description	Roughtop
Bottom Cover Compound	Bare RFL
Bottom Cover Description	Bare
Carcass Type	Polyester
Carcas Compound	Tan SBR
Number of Plies	2

Product Characteristics

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Technical Data

Minimum Pulley Diameter	2.00 in
Top Cover Thickness (in)	0
Bottom Cover Thickness (in)	0
Overall Gauge (in)	9/32 in (7.14 mm)
Unit Weight- lb/PIW	0.1000 lbs/PIW
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	-40 °F
Tension Rating (PIW)	150 PIW

Joining Related Properties

Splice Step	Yes
Splice Finger	No
Flexco Plate/Rivet	
Flexco Hinged	
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#1



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

WWW.midwestrubber.com