

General Information

715 2 Ply Black SBR 150 Smooth C X B

MWR Part#	715
Description	2 Ply Black SBR 150 Smooth C X B
Additional Specifications	10454 #52
Special features	High-tension synthetic fabrics result in minimum stretch, great fastener holding ability, impact resistance and the highest adhesion between plies and cover.
Product Category	Pacakge Handling
Main industry segments	Automotive, aviation, industrial, logistics, manufacturing, materials handling, package handling, packaging and parcel handling.
Applications	Excellent abrasion resistance and flex life and is the best buy for the majority of conveyor belt applications



Product Construction Design

Top Cover Compound	SBR
Top Cover Color	Black
Top Cover Description	Smooth
Bottom Cover Compound	Poly/Nylon
Bottom Cover Description	Bare
Carcass Type	Poly/Nylon
Carcas Compound	Black SBR
Number of Plies	2

Product Characteristics

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Technical Data

Minimum Pulley Diameter	6.00 in
Top Cover Thickness (in)	1/32 in (0.80 mm)
Bottom Cover Thickness (in)	0
Overall Gauge (in)	1/8 in (3.18 mm)
Unit Weight- lb/PIW	0.0690 lbs/PIW
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F
Tension Rating (PIW)	150 PIW

Joining Related Properties

Splice Step	Yes (Hot Step 8" Step Size)
Splice Finger	No
Flexco Plate/Rivet	
Flexco Hinged	
Alligator Staple	#125
Clipper Lace	#2
Alligator Lace	#15



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

WWW.midwestrubber.com