

**General Information****718 3 Ply Black SBR 150 Roughtop C X B**

MWR Part#	718
Description	3 Ply Black SBR 150 Roughtop C X B
Additional Specifications	1612(24)(37A-0).040
Applications	
Product Category	
Main industry segments	
Special features	

**Product Construction Design**

Conveying side material	SBR
Conveying side surface	Roughtop
Conveying side property	
Conveying side color	Black
Traction layer (material)	
Number of Plies	3
Pulley side material	Fabric
Pulley side surface	Bare
Pulley side property	
Pulley side color	

**Product Characteristics**

Antistatically equipped	No
Food suitability, FDA conformance	No

**Technical Data**

Thickness of belt	8.36 mm, 0.329 in
Mass of belt (belt weight)	6.83 kg/m <sup>2</sup> , 1.4 lbs/ft <sup>2</sup>
Elongation at 2%	40.3 N/mm, 225 lbs/in
operating temperature Range F	-40° to 250°
operating temperature C	-40° to 121°

**Joining Related Properties**

Primary Joining method	Overlap Splice
Secondary Joining method	Mechanical Lace
Minimum Pulley Diameter	3.0 in, 63.6 mm



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

[www.midwestrubber.com](http://www.midwestrubber.com)