

**General Information****755 2 Ply White PU Fabric C X C**

|                           |                             |
|---------------------------|-----------------------------|
| MWR Part#                 | 755                         |
| Description               | 2 Ply White PU Fabric C X C |
| Additional Specifications | 110310 U0/2ES White         |
| Applications              |                             |
| Product Category          |                             |
| Main industry segments    |                             |
| Special features          |                             |

**Product Construction Design**

|                           |                       |
|---------------------------|-----------------------|
| Conveying side material   | Spun Polyester Fabric |
| Conveying side surface    | PU Impregnated        |
| Conveying side property   |                       |
| Conveying side color      |                       |
| Traction layer (material) | Spun Polyester Fabric |
| Number of Plies           | 2                     |
| Pulley side material      | Spun Polyester Fabric |
| Pulley side surface       | PU Impregnated        |
| Pulley side property      |                       |
| Pulley side color         | White                 |

**Product Characteristics**

|                                   |     |
|-----------------------------------|-----|
| Antistatically equipped           | No  |
| Food suitability, FDA conformance | Yes |

**Technical Data**

|                               |   |
|-------------------------------|---|
| Thickness of belt             | 1.30 mm, 0.051 in                               |
| Mass of belt (belt weight)    | 1.2 kg/m <sup>2</sup> , .25 lbs/ft <sup>2</sup> |
| Elongation at 1%              | 6 N/mm, 34.26 lbs/in                            |
| operating temperature range C | -30/80 °C                                       |
| operating temperature range F | -22/176 °F                                      |
| Seamless manufacturing width  | 3,169 mm, 124.75 in.                            |

**Joining Related Properties**

|   |                      |
|---|----------------------|
| Primary Joining method                              | Finger               |
| Secondary Joining method                            | Clipper® UCM36SL XSP |
| Minimum Pulley/Nose Bar Diameter for Endless Splice | 10.00 mm, 0.394 in.  |
| Minimum Back Flex                                   | 10.00 mm, 0.394 in.  |



**Application specialists are ready to help — call 763-559-2551. On-site installation team available.**

[www.midwestrubber.com](http://www.midwestrubber.com)