

General Information**778-9 1 Ply Red PU 150 Smooth C X FS**

MWR Part#	778-9
Description	1 Ply Red PU 150 Smooth C X FS
Additional Specifications	IG-150/85 COS
Applications	Ideal for slider bed applications.
Product Category	Heavy Duty Industrial Grade Conveyor Belting
Main industry segments	
Special features	All-polyester solid woven carcass, offering enhanced strength and durability for industrial applications. Engineered to withstand demanding environments. Superior resistance to abrasion, cutting, and gouging, along with exceptional protection against oils, greases, and hydrocarbon solvents.

Product Construction Design

Conveying side material	Polyurethane 85 Durometer
Conveying side surface	Smooth Glossy
Conveying side property	
Conveying side color	
Traction layer (material)	Polyester solid woven carcass
Number of Plies	1
Pulley side material	Poyester Fabric
Pulley side surface	Friction Surface
Pulley side property	
Pulley side color	

Product Characteristics

Antistatically equipped	No
Food suitability, FDA conformance	Yes

Technical Data

Thickness of belt	1/4"
Weight per foot	0.133#
Tension Rating (PIW)	150
Operating temperature range	0 ° - 185°
Seamless manufacturing width	114"

Joining Related Properties

Primary Joining method	Finger Splice, Hot Air Welding
Mechanical Fasteners Flexco	#187, R4
Minimum Pulley Diameter	6"



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

www.midwestrubber.com

6"