825 2 Ply Green NBR Rough C X C **General Information** MWR Part# Description 2 Ply Green NBR Rough C X C **Product Category** Machine Tapes H010100255 F-0 **Additional Specifications** Paper manufacturing and processing, Paper printing and finishing Main industry segments **Applications** Machine tape, Paper handling belt, Processing belt Special features Abrasion resistant, Constant and gentle positive grip, Constant coefficient of friction, Forgiving in case of short term shock like overloads, Versatile, Outstanding flex-fatigue **Product Construction Design** Acrylonitrile-Butadiene-Rubber (NBR) Conveying side material Conveying side surface Rough structure Adhesive Conveying side property Conveying side color Green Traction layer (material) Polyamide (PA) Number of Fabrics Acrylonitrile-Butadiene-Rubber (NBR) Pulley side material Pulley side surface Impregnated fabric Pulley side property Non-adhesive Green Pulley side color **Product Characteristics** Antistatically equipped Yes Adhesive free joining method No Food suitability, EU conformance No Food suitability, FDA conformance No 0.70 mm (0.03 inch) Mass of belt (belt weight) 0.70 kg/m² (0.143 lb/sqft) Tensile force for 1% elongation (k1% static) 4.6 N/mm (26 lbf/in)

Technical Data
Thickness of belt

Tensile force for 1% elongation (k1% relaxed)

Min. operating temperature admissible (continuous) Max. operating temperature admissible (continuous)

Seamless manufacturing width

1.8 N/mm (10 lbf/in)

-20 °C (-4 °F)

100 °C (212 °F)

1140 mm (44.88 inch)

Joining Related Properties

Joining method	Thermofix 75°	
Pulley diameter (minimum)	20 mm (0.79 inch)	
Pulley diameter minimum with counter flection	20 mm (0.79 inch)	
· ·		

Application Suitability

- Approaches actions of the control		
Slider bed suitable	Yes	
Carrying rollers suitable	Yes	
Troughed installation suitable	No	
Mode of use or conveyance	Declined, Horizontal, Inclined, Twists, Twists with short center distance,	
	Vertical	

