

General Information**860-68 2 Ply Clear PU Smooth C X B**

MWR Part#	860-68
Description	2 Ply Clear PU Smooth C X B
Additional Specifications	4-4600: U2C Urethane-HD
Applications	Metal stamping, recycling of glass cullet, die cutting, brick manufacturing
Product Category	TPU conveyor belt
Main industry segments	Handles impact and abrasion from metal, glass, aluminum, ateel rule dies
Special features	2 ply polyester carcass with tough Urethane cover

**Product Construction Design**

Conveying side material	Polyurethane 92A
Conveying side surface	Smooth
Conveying side property	
Conveying side color	Clear
Traction layer (material)	Polyester Fabric
Number of Plies	2
Pulley side material	Polyurethane
Pulley side surface	Bare
Pulley side property	
Pulley side color	

Product Characteristics

Antistatically equipped	Yes
Food suitability, FDA conformance	No

Technical Data

Thickness of belt	0.157" +/- 0.02"
Mass of belt (belt weight)	0.09 lbs./PIW
Elongation	Less than 1%
Work Tension	150 lbs./PIW
Working Temp	0 to 180
Seamless manufacturing width	118.11"

Joining Related Properties

Primary Joining method	Finger
Minimum Pulley	4"
Backflex Min. Pulley Dia.	6"

Application Suitability

Slider bed suitable	Yes
---------------------	-----



Application specialists are ready to help — call 763-559-2551. On-site installation team available.

www.midwestrubber.com